

# U1

## Full Color LED Video Processor

Version: v2.3

Release Date: November 2021



## Specification



TEL 400 159 0808  
Web: [www.kystar.com.cn](http://www.kystar.com.cn)

**Beijing KYSTAR Technology Co., Ltd.**


Professional Ultra HD Video Display  
Control system integrated solution and service provider

# Video processor U1 product specification

## Summary

The U1 is designed to address the limitations of large screen control systems in image processing, picture control and signal format conversion. The industry's top design technology is in line with international and industry standards.


The whole machine can carry 1920 x 1200 load, which can meet the needs of most small and medium-sized projects.



## Functional characteristics

- 2 channel programming output channel, the most wide band of 1920 pixels, with a maximum load of 1200 pixels.
- Any part of the signal source is intercepted and displayed.
- Support multiple high definition signal inputs
- Executable offline planning tasks
- can save 5 scene modes, one key call.
- Support direct cut and fade in, no black screen, caton.
- Panel recognition source status.
- Support one button black screen / static.
- Support PC software control.
- Support brightness 0-255 adjustment
- Two LED sending cards can be built.

## Panel description



Serial number	Functional description
①	Power switch
②	Full color LCD information screen
③	Signal source quick select area
④	Function button area
⑤	Parameter setting and debugging area
⑥	Knob adjustment

## Port specification




Input port		
Type	Number	Specifications
CVBS ( BNC )	2	NTSC/PAL adaptive, 3D comb filter support
VGA	1	VESA standard, maximum support 1920 * 1080@60Hz
DVI	1	The maximum support is 1920 x 1200@60Hz, compatible with HDMI1.3 and the following versions.
HDMI	1	Compatible with HDMI1.3 and below
USB	1	USB2.0, support USB offline play.

Output port		
Type	Number	Specifications
DVI-D	2	Maximum horizontal resolution 1920 pixels Vertical resolution up to 1200 pixels


Control port		
Type	Number	Specifications
USB-CFG	1	USB Type B
UART (RJ-45 )	1	IN&OUT, serial port protocol

Specification for whole machine	
Input power supply	100-240V AC~50/60Hz 0.6A
working temperature	0-45°C
Shape size	483×283×72mm (L×W×H )
Net weight	4KG
Complete machine power consumption	36W


## Appendix: equipment size drawing



**Front size map**



**Back size drawing**



**Side size drawing**